


NEOCEMENT®

WALL TO FLOOR
CEMENT FINISHES



200/127-Powder



200/127-Powder
+ Metallo R Silver (NT+2 / Kg)



200/128-Screed



200/128-Screed
+ Metallo R Silver (NT+2 / Kg)



200/129-Pencil



200/129-Pencil
+ Metallo R Silver (NT+2 / Kg)

ENG

Neocement®

Neocement® is a tri-component decorative polished cement finish that is trowel applied, suitable for application over a multitude of architectural surfaces mainly walls and floors. Neocement® can also be colored and designs can be incorporated to achieve completely customizable and unique effects thus providing interior designers with a wide array of bespoke and modern finishes options.

Technical Name

Polished cement.

Key Properties

- High strength with impact and abrasion resistance
- Antistatic and fire resistance
- Moisture vapor permeable and excellent water resistance
- Flexible flooring
- Low VOC Technology
- Seamless flooring option
- Wide range of colors, textures and patterns
- Extends life-cycle appearance of concrete
- 3 Hours working life

Pack Size

- 14 kg paste + 8.3 kg Filler + 2.8 kg Resin
- 2.33kg paste + 1.38kg Filler + 0.47kg Resin

Recommended Uses

Neocement® is suitable for Interior and exterior on horizontal and vertical surfaces.

Type of Substrate

Neocement® can be applied on a multitude of surfaces such as concrete, wood, metal, marble, granite, ceramic tiles and even glass.

Finish

Mid sheen polished finish.

Coverage

Approximately 1 m²/kg depending on application technique.

Drying Time

Open to light traffic after 24 hours. Full cure in 72 hours depending on weather conditions and ambient temperature.

Thinner

No thinning required.


Preparation

All surfaces to be painted should be repaired, clean, dry and free from loose and flaking material. Then the surfaces should be sanded smooth, dusted clean and primed with a suitable COLORTEK® primer.

Instructions

- Apply SX0 PrimeWell or SX9 HmiGuard to consolidate the surface. On ceramic apply a coat of Neogrip.
- Apply Neofiller Base Coat (two coats). Once the second coat has dried, sand the surface with a 60 grid and remove the dust.

CODING SYSTEM



- Apply first Neocement Coat; (Mix all 3 components until obtaining a relatively pasty mortar with good sag resistance).
- Once the coat has dried, apply second Neocement coat.
- Once the second coat has dried, sand the surface with a 150 or 220 grid and remove the dust.
- Apply the desired protective topcoat depending on intended use of the surface and location.
- When applying on ceramic tiles, it is important to remove or block the joint tiles with COLORTEK® SX2.

Note: Use a stainless steel trowel for a marble like polished cement finish or a sponge-covered trowel to obtain a Venetian rustic effect.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. **Do not empty product into drains or watercourses.**

Additional Info

Product batches are tested using a quality control system and are ISO 9001:2008 certified.

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost and humidity.



FR

Neocement®

Neocement® est un revêtement décoratif tri-composant donnant un aspect de béton ciré applicable à la truelle sur une multitude de surfaces architecturales principalement les murs et sols. Neocement® peut également être teinté et des motifs décoratifs peuvent être incorporés dans le design final pour obtenir des effets décoratifs uniques, offrant ainsi aux architectes d'intérieur un large éventail de finitions.

Nom Technique

Béton ciré.

Propriétés

- Haute résistance aux chocs et à l'abrasion
- Résistance antistatique et au feu
- Perméable à la vapeur d'eau
- Protège contre la pénétration de l'eau, des chlorures et CO₂
- Propriétés supérieures d'adhérence
- Flexible
- Très faible contenant en COV
- Finition sans jointure
- Vaste choix de couleurs, textures et motifs
- Temps ouvert 3 heures

Emballage

- 14 kg pâte + 8.3 kg Filler + 2.8 kg Resine
- 2.33kg pâte + 1.38kg Filler + 0.47kg Resine

SYSTÈME DE CODAGE



Usage Recommandé

Neocement® est applicable à l'intérieur et l'extérieur sur des surfaces horizontales et verticales dans des endroits tels que les cuisines, les salles de bains, les cabines de douche ou même les baignoires. Adapté pour les zones à fort trafic.

Types de Support

Neocement® peut être appliqué sur une multitude de surfaces telles que le béton brute, le bois, le métal, le granite, la céramique ou même le verre.

Finition

Satinée.

Rendement

Approximativement 1 m²/kg en fonction de la technique d'application.

Temps de Séchage

24h pour le trafic léger et 72 h pour le durcissement complet en fonction des conditions climatiques et de la température ambiante.

Diluant

Aucune dilution requise.

Préparation du Support

Le support doit être dur, propre, sain, sec, cohésif et libre de toute matière telle que salpêtre, mousse, lichen ou autres microorganismes pouvant empêcher l'adhérence du produit sur le support.

Application

- Appliquez une couche de SX0 PrimeWell ou SX9 HmiGuard afin de consolider les surfaces friables ou poreuses. Sur céramique application de Neogrip est recommandé.
- Appliquez Neofiller en deux couches tout en laissant un temps de séchage approprié entre les deux couches.
- Une fois la base de Neofiller sèche, poncer la surface et enlever la poussière.
- Appliquez Neocement en deux couches tout en laissant un temps de séchage approprié entre les deux couches.
- Une fois la seconde couche sèche, poncer la et nettoyer la surface.
- Appliquez la protection appropriée en fonction de l'usage.
- Lorsque l'application se fait sur de la céramique ou du carrelage, il est important de traiter les jointures avec COLORTEK® SX2.

Note: Utiliser une truelle en acier inoxydable pour une finition de béton ciré brillant ou une truelle recouverte d'une éponge pour une finition rustique.

Nettoyage des Outils

Éliminer autant que possible le reste du produit de la surface des outils. Nettoyer ces derniers en les frottant vigoureusement avec de l'eau et du savon.

Ne pas vider les restes du produit dans égouts ou les voies d'eau.

Information Additionnelle

Le processus de fabrication de Neocement® est soumis au plus stricts contrôles de qualité certifiés conformes au standard ISO 9001:2008.

Transport et Stockage

Stocker le produit à l'abri de l'humidité et des températures de gel.




www.colortek.eu
info@colortek.eu




Synergy, Added Value, Continuous Improvement,
Diversity, Integrity, Social Responsibility.



200/00-Castle White



200/103-Vapor



200/106-Canvas




200/106-Canvas
+ Metallo R Silver (NT+2 / Kg)




200/109-Paper



200/112-Urban



200/115-Steam



200/115-Steam
+ Metallo R Silver (NT+2 / Kg)



200/118-Ashes



200/121-Loft




200/124-Horizon




200/124-Horizon
+ Metallo R Silver (NT+2 / Kg)



200/101-Neutral



200/104-Cloud



200/107-Dust



200/107-Dust
+ Metallo R Silver (NT+2 / Kg)




200/110-Attic




200/113-Slab



200/116-Sidewalk




200/116-Sidewalk
+ Metallo R Silver (NT+2 / Kg)




200/119-Cast



200/122-Fusion




200/125-Cork



200/125-Cork
+ Metallo R Silver (NT+2 / Kg)



200/102-Raw



200/105-Stone




200/108-Terre




200/108-Terre
+ Metallo R Silver (NT+2 / Kg)



200/111-Depth



200/114-Refined



200/117-Wetcement




200/117-Wetcement
+ Metallo R Silver (NT+2 / Kg)




200/120-Element



200/123-Slate



200/126-Onyx



200/12-Onyx
+ Metallo R Silver (NT+2 / Kg)